

LCS-II Fact Sheet

Specification

LCS-II Porcelain

Enamel Steel Specification:

The surface of the cold rolled steel, specially processed for temperatures used in coating porcelain on steel, is precleaned to ensure bond between the steel and the porcelain surface. After precleaning, during a 3-coat process, both steel surfaces receive a ground coat of porcelain enamel. Then, a color cover coat of porcelain is applied to one surface of the ground coat and is fusion bonded to the steel substrate at a temperature necessary to reduce steel and porcelain stresses, but no less than 1200 degrees F. LCS-II, with low gloss, can be used as a projection surface.

Life of Building Guarantee

Under normal usage and maintenance, and when installed in accordance with Claridge instructions and recommendations, Claridge LCS-II porcelain enamel steel markerboard writing surfaces are guaranteed for the life of the building. Guarantee covers replacement of defective boards but does not include cost of removal or reinstallation.

Features

- Writes easily
- Erases cleanly (dry-erase)
- Low gloss
- Can be used as a projection surface
- Minimal "hot spot"
- Magnetic
- Colorfast
- Highly scratch and stain resistant
- Long-wearing surface
- Smooth, velvety touch

Your local stocking distributor is

 **PBS SUPPLY CO.**
7013 So 216th St - Kent, WA 98032
Ph 1-877-727-7515 Fax 253-395-5575
www.pbssupply.com

870.743.2200

www.claridgeproducts.com

601 Highway 62-65 South / P.O. Box 910
Harrison, AR 72602-0910

